

## Rozvádzač na povrchovú montáž

Typ	Rozmery**					Pde*	Statická záťaž
	A	B	C	D	E		
ECT4PT/ECT4PO	235 mm	143 mm	98 mm	127 mm	46 mm	>10 W	520 g
ECT8PT/ECT8PO	236 mm	215 mm	102mm	107 mm	120 mm	>16 W	1040 g
ECT12PT/ECT12PO	236 mm	287 mm	112 mm	107 mm	180 mm	>25 W	1560 g
ECT18PT/ECT18PT	236 mm	396 mm	112 mm	107 mm	289 mm	>25 W	2340 g
ECT24PT/ECT24PO	361 mm	287 mm	112 mm	232 mm	180 mm	>30 W	1560 g
ECT36PT/ECT36PO	485 mm	287 mm	112 mm	357 mm	180 mm	>30 W	1560 g
ECT48PT/ECT48PO	652 mm	287 mm	112 mm	482 mm	180 mm	>35 W	1560 g
ECT2x18PT/ECT2x18PO	361 mm	396mm	112 mm	232 mm	289 mm	>30 W	2340 g
ECT3x18PT/ECT3x18PO	526 mm	396mm	112 mm	357 mm	289 mm	>35 W	2340 g
ECT4x18PT/ECT4x18PO	651 mm	396mm	112 mm	357 mm	289 mm	>40 W	2340 g

\*Maximálne povolené straty výkonu pri inštalácii maximálneho počtu zariadení

\*\*Veľkosti platia aj pre IT rozvádzače DIDO-E MEDIA: ECT...MEDIA

